



RELOCK P/N	DIM A	TOL.
CG-10-04-24	24	±0.125
CG-10-04-36	36	±0.125
CG-10-04-50	50	±0.125
CG-10-04-72	72	±0.125
CG-10-04-100	100	±0.125
CG-10-04-120	120	±0.188
CG-10-04-150	150	±0.188
CG-10-04-180	180	±0.188
CG-10-04-240	240	±0.25

NOTES:

1. CABLE TO HAVE MINIMUM BREAK STRENGTH 160LBS
2. TENSILE STRENGTH MINIMUM 1960N/mm²
3. ZINC DIE CAST TO BE ZAMAK 5

<small>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES .XX = ±.01 .XXX = ±.005 ANGLES = ±1° BREAK ALL EDGES 0.005 MIN SURFACE FINISH 63 MICRO INCHES DIMENSIONS APPLY AFTER FINISH CONCENTRICITY = 0.025 TIR</small>		NAME	DATE	<h1>RELOCK SUSPENSION</h1>				
	DRAWN	RYAN KWAST	1/23/2025		TITLE			
	CHECKED				<h2>1.0MM 7X7 GALVANIZED CABLE W #04 ZINC DIE CAST BALL END</h2>			
	APPROVED							
DO NOT SCALE DRAWING				SIZE				
BREAK ALL SHARP EDGES AND REMOVE BURRS				DWG NO.	CG-10-04-XXX	REV.		
THIRD ANGLE PROJECTION	MATERIAL	FINISH		SCALE	1:1	WEIGHT	SHEET	1 of 1
	VARIOUS	VARIOUS						